

...connecting to the aftermarket

CTSDF001.2

DAF Trucks Steering Wheel Control Interface













Vehicle Application

DAF XF 2017>

For Trucks with Quadlock Connector Only

Key Features

- Retains Steering Wheel Controls (if equipped)
 - Retains OEM USB Port (if equipped)
 - Retains OEM Aux Port (if equipped)
 - Provides Illumination Feed (in harness)





ABOUT THIS PRODUCT

CTSDF001.2

CAN-Bus Steering Wheel Control Interface for XF/CF DAF trucks with quadlock connector.

NB: After installation, radio information on the cockpit display (eg. radio station names, RDS information) will be lost.

Black

Red

WIRING COLOUR CODES

Right Rear Speaker + Purple Purple/Black Right Rear Speaker -Green Left Rear Speaker + Green/Black Left Rear Speaker -Grev Right Front Speaker + Grey/Black Right Front Speaker -White Left Front Speaker + White/Black Left Front Speaker -

Yellow Permanent 12V Ground Ianition 12V Orange Illumination

PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. Connects2 can not be held responsible for the installation of this product.

TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at **support.connects2.com** and provide as much information as possible.

FOLLOW US ON SOCIAL MEDIA for all the latest updates



CONNECTS2 Watch us on YouTube



/CONNFCTS2 Like us on facebook



CONNECTS2LTD Follow us on instagram







FITTING GUIDE

- 1. Remove and disconnect the original head unit.
- 2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.





FITTING GUIDE

- 6. Connect the male USB connector and 3.5mm jack connector from the interface to the aftermarket stereo to retain the vehicle's OEM USB and Aux inputs (if equipped)
- 7. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation.

Interface not working?

- 1. Turn off all power to your vehicle's system and remove the interface
- 2. Open the interface box casing to reveal dipswitches on the interface board
- 3. Dipswitch 1 is set to 'On' by default. Set Dipswitch 1 to 'Off' and Dipswitch 2 to 'On'
 - 4. Repeat Steps 2-7 and test for correct operation

STEERING WHEEL CONTROL FUNCTIONALITY

NB: The phone buttons on the steering wheel will still continue to operate the OEM Bluetooth phone kit if the vehicle is equipped

Original Button	Function
1	Volume +
2	Volume -
3	Track +
4	Track -

